










名称	级别	规格	符号	数量	重量(kg)	备注
螺	6.8级	M16X40		21	3.0	
		M16X50		6	1.0	
		M16X60		1	0.2	
		M16X70S		4	0.9	带双帽
		M20X45		20	5.4	
柱		M20X80S		16	6.6	带双帽
脚	6.8级					
钉						
垫圈	Q235	-3($\phi 17.5$)				
合计			规格×数量	6	0.1	
		17.2 kg				

编 号	规 格	长 度 (mm)	数 量	重 量 (kg)		备 注
				一 件	小 计	
401	Q345L70X6	3079	1	19.72	19.7	局部合角
402	Q345L70X6	3079	1	19.72	19.7	局部合角
403	Q345L70X6	3054	1	19.56	19.6	局部开角 切角
404	Q345L70X6	3054	1	19.56	19.6	局部开角 切角
405	L40X3	1170	2	2.17	4.3	
406	L40X3	854	1	1.58	1.6	切角
407	L40X3	854	1	1.58	1.6	切角
408	L40X3	1112	2	2.06	4.1	
409	L40X3	452	1	0.84	0.8	切角
410	L40X3	452	1	0.84	0.8	切角
411	Q345-8X241	449	1	6.80	6.8	卷边50mm
412	Q345-8X241	449	1	6.80	6.8	卷边50mm
413	L50X4	1188	1	3.63	3.6	
414	L50X4	1188	1	3.63	3.6	切角
415	L45X4	1645	1	4.50	4.5	切角
416	L45X4	1645	1	4.50	4.5	
417	L45X4	1227	1	3.36	3.4	切角
418	L45X4	1227	1	3.36	3.4	
419	Q345L75X6	712	1	4.92	4.9	用于UB板连接
420	Q345L75X6	688	1	4.75	4.8	用于UB板连接
419A	Q345L75X6	712	1	4.92	0.0	用于U ₁ 螺栓连接
420A	Q345L75X6	688	1	4.75	0.0	用于U ₁ 螺栓连接
421	-6X133	166	2	1.04	2.1	
422	Q345-22X382	340	1	22.43	22.4	火曲
423	Q345-22X382	340	1	22.43	22.4	火曲
424	L40X3	1755	1	3.25	3.2	
425	L40X3	1755	1	3.25	3.2	切角
426	L40X3	1639	1	3.04	3.0	
427	L40X3	1639	1	3.04	3.0	切角
428	L40X3	1062	1	1.97	2.0	
429	Q345L70X6	150	2	0.96	1.9	用于UB板连接
430	-8X50	50	1	0.16	0.2	垫板
431	-16X50	50	1	0.31	0.3	垫板
合 计			201.8 kg			



日期	签名	姓名	专业




1C1W9-J2-05

1C1W9-J2单回路转角塔
外角侧导线横担(4)结构图