













螺栓、脚钉、垫圈明细表							构件明细表						
名称	级别	规格	符号	数量	重量(kg)	备注	编号	规格	长度(mm)	数量	重量(kg)		备注
											一件	小计	
螺		M16X40		111	16.0		601	Q345L100X8	4202	1	51.58	51.6	带脚钉
		M16X50		43	6.9		602	Q345L100X8	4202	1	51.58	51.6	
		M16X60		4	0.7		603	Q345L100X8	4202	1	51.58	51.6	带脚钉
	6.8级	M20X45		88	23.8		604	Q345L100X8	4202	1	51.58	51.6	
		M20X55		126	37.2		605	Q345L110X8	610	4	8.25	33.0	清根
柱							606	Q345L70X5	2227	2	12.02	24.0	切角
							607	Q345L70X5	2227	2	12.02	24.0	
							608	Q345L70X5	2031	2	10.96	21.9	切角
							609	Q345L70X5	2031	2	10.96	21.9	
							610	Q345L70X5	1551	2	8.37	16.7	局部合角
脚钉		M16X180		7	2.3		611	Q345L63X5	1774	4	8.55	34.2	
	6.8级	M20X200		3	1.9		612	Q345L63X5	1389	2	6.70	13.4	局部开角
垫圈 Q235		-3(φ17.5)		8	0.1		613	Q345L63X5	222	4	1.65	6.6	
		-4(φ22)		12	0.3		614	Q345-8X446	537	1	15.04	15.0	火曲
							615	Q345-8X446	537	1	15.04	15.0	火曲
合 计		89.2 kg											
		616 Q345L75X6 495 1 3.42 3.4 火曲											



编 号	规 格	长 度 (mm)	数 量	重 量 (kg)		备 注
				一 件	小 计	
601	Q345L100X8	4202	1	51.58	51.6	带脚钉
602	Q345L100X8	4202	1	51.58	51.6	
603	Q345L100X8	4202	1	51.58	51.6	带脚钉
604	Q345L100X8	4202	1	51.58	51.6	
605	Q345L110X8	610	4	8.25	33.0	清根
606	Q345L70X5	2227	2	12.02	24.0	切角
607	Q345L70X5	2227	2	12.02	24.0	
608	Q345L70X5	2031	2	10.96	21.9	切角
609	Q345L70X5	2031	2	10.96	21.9	
610	Q345L70X5	1551	2	8.37	16.7	局部合角
611	Q345L63X5	1774	4	8.55	34.2	
612	Q345L63X5	1389	2	6.70	13.4	局部开角
613	Q345-6X158	222	4	1.65	6.6	
614	Q345-8X446	537	1	15.04	15.0	X轴
615	Q345-8X446	537	1	15.04	15.0	X轴
616	Q345L75X6	495	1	3.42	3.4	X轴
617	Q345L75X6	495	1	3.42	3.4	X轴
618	Q345-8X446	537	1	15.04	15.0	X轴
619	Q345-8X446	537	1	15.04	15.0	X轴
620	Q345L70X6	495	1	3.17	3.2	X轴
621	Q345L70X6	495	1	3.17	3.2	X轴
622	Q345-8X315	474	1	9.38	9.4	X轴
623	Q345-8X315	474	1	9.38	9.4	X轴
624	Q345-8X315	477	1	9.44	9.4	X轴
625	Q345-8X315	477	1	9.44	9.4	X轴
626	L56X5	2222	2	9.45	18.9	切角
627	L56X5	2222	2	9.45	18.9	
628	L56X5	2036	2	8.66	17.3	切角
629	L56X5	2036	2	8.66	17.3	
630	L56X5	1552	2	6.60	13.2	局部合角
631	L56X5	1799	4	7.65	30.6	
632	L56X4	1389	2	4.79	9.6	局部开角
633	-6X148	210	4	1.46	5.8	
634	-6X232	292	4	3.19	12.8	
635	-6X211	290	4	2.88	11.5	
636	L50X4	1051	4	3.22	12.9	
637	L40X3	1616	1	2.99	3.0	
638	L40X3	1650	1	3.06	3.1	
639	-6X224	220	1	2.32	2.3	
640	-6X219	220	1	2.27	2.3	
641	-6X148	236	2	1.65	3.3	
642	L40X4	2037	2	4.93	9.9	
643	-6X101	332	4	1.58	6.3	
644	-10X60	60	4	0.28	1.1	垫板
645	-10X50	50	4	0.20	0.8	垫板
646	-8X50	50	4	0.16	0.6	垫板
合 计				714.4	kg	

1C1M9-J2单回路转角塔

身体结构图




1C1W9-J2-07