









编 号	规 格	长 度 (mm)	数 量	重 量 (kg)		备 注
				一 件	小 计	
801	Q345L25X10	5686	1	108.79	108.8	带翻打
802	Q345L125X10	5686	3	108.79	326.4	
803	Q345L110X8	630	4	8.53	34.1	铲背
804	Q345-8X115	630	8	4.55	36.4	
805	Q345.63X5	4594	4	22.15	88.6	切角
806	Q345.63X5	4594	4	22.15	88.6	
807	L40X3	1100	8	2.04	16.3	切角
808	L40X3	1384	8	2.56	20.5	切角
809	L40X3	1260	4	2.33	9.3	切角
810	L40X3	1260	4	2.33	9.3	
811	Q345.63X5	2205	4	10.63	42.5	切角
812	Q345.63X5	2205	4	10.63	42.5	
813	L40X3	832	8	1.54	12.3	
814	L40X3	948	8	1.76	14.1	
815	Q345.63X5	2956	4	14.25	57.0	扁开角
816	Q345.63X5	2020	4	9.74	39.0	
817	Q345.63X5	2020	4	9.74	39.0	切角
818	L40X3	1020	8	1.89	15.1	
819	L40X3	832	8	1.54	12.3	
820	Q345-6X248	288	8	3.36	26.9	
821	Q345-6X337	362	4	5.75	23.0	卷50mm
822	Q345.63X5	2239	4	10.80	43.2	
823	L40X4	1671	2	4.05	8.1	
824	L50X4	1014	4	3.10	12.4	
825	-6X100	365	4	1.72	6.9	
826	-10X60	60	4	0.28	1.1	型板
805A	Q345.63X5	4414	4	21.28	0.0	用于挖3段
806A	Q345.63X5	4414	4	21.28	0.0	用于挖3段

螺栓、脚钉、垫圈明细表						
名称	级别	规格	符号	数量	重量(kg)	备注
螺栓	6.8级	M16x40		84	12.1	
		M16x50		28	4.5	
		M20x45		68	18.4	
		M20x55		68	20.1	
		M20x65		96	30.8	
脚钉	6.8级	M16x180		12	3.9	
		M20x200		2	1.2	
垫圈	Q235					
合 计			规格X个数			
					91.0 kg	

说明: (805A) (806A) 用于接1了段.

日期	冬季	春季	夏季

[illegible]